Item No. 1-16
Mr. Miller
Date: 1/20/05

REVISION TO 2006 STANDARD SPECIFICATIONS

SECTION 910, BEGIN LINE 1016, DELETE AND INSERT AS FOLLOWS:

4. Barbed Wire

Barbed wire used at the top and bottom of farm field fence, or as otherwise specified, and in accordance with 603 shall be in accordance with applicable provisions of ASTM A 121. It shall be composed of No 12 1/2 gage (2.5 mm) galvanized or aluminum coated steel wire with four round 14 gage (2.0 mm) barbs at approximately 5 in. (125 mm) spacing. The galvanized coating shall be in accordance with class 3 in Table 3 2. The minimum aluminum coating weights (mass) shall be 0.30 and 0.25 oz/sq ft (91.5 and 76.3 g/m²) on the 12 1/2 gage (2.5 mm) wire and 14 gage (2.0 mm) barbs respectively in accordance with class 60 for the line wire and class 20 for the barb wire. The weight (mass) of coating shall be determined in accordance with ASTM A 428. The use of aluminum barbs, in accordance with ASTM B 211 (B 211M), alloy 5052-H38, nominal diameter 0.080 in. No. 14 gage (2.03 mm), will be permitted.

The use of barbed wire with No. 15 1/2 gage (1.70 mm), high tensile strength line wires, and No. 16 1/2 gage (1.5 1.47 mm) barbs will be permitted. The barbs shall be round with four points and spaced at approximately 5 in. (125 mm) intervals. The barbed wire shall be in accordance with ASTM A 121, except the minimum weight (mass) of zinc coating shall be 0.75 oz/sq ft (229.0 g/m²) for line wires and 0.70 oz/sq ft (214.0 g/m²) for barbs. The galvanized coating shall be in accordance with class 3 in Table 2.

Other sections containing specific cross references:	General Instructions to Field Employees Update Required? Y N By - Additional or Revision
713.02 Pg 517	Frequency Manual Update Required? Y N By - Addition or Revision
Recurring Special Provisions potentially affected:	Standard Sheets potentially affected:
	NONE
NONE	
Motion: Mr. Second: Mr. Ayes: Nays:	Action: Passed as submitted; revised Effective Letting Supplementals
	Withdrawn. Resubmit?
	Received FHWA Approval?